

# OILSORB PG

## ANTI-SLITHERING ABSORBENTS

**OILSORB PG** is a silicate and carbonate mixture , particularly indicated to solve any kind of problem which accidental loss of dangerous or slippery liquids , concluding rapidly an absorption action , both natural and chemical.

### Chemical-Physical Properties

Appearance	Granules
Colour	White
Density	500 g/l
Average dimension	0.8 - 2.0 mm 2.0 - 4.8 mm
Oil absorption	90%

values can be subject to minor variations

### Applications

**OILSORB PG** is suitable for road coats maintenance , highways , parking places , car parks , garages , repair shops , runways , gas distributors , laboratories , food industry etc.

### Dosage and Modality of use

Spread the product on the surface to treat, brush with shovels or brooms , picking up the product already grey-coloured and impregnated . In case of old stains or big quantities of liquids to be absorbed , should be made a second treatment.

### Packing

The product is supplied in 5 kg bags.

### Storage

**OILSORB PG** can be stored for 36 months in its original closed packages.

### Warning

**OILSORB PG** does not present risks. For more information on classification and measures of protection, please see the Safety Data Sheet available upon request.

The present card contains technical information of our products at our best knowledge. STAR ASPHALT S.p.A. assumes responsibility exclusively for the applications carried out under its directly supervision.

STAR ASPHALT S.p.A.

Strada Prov. Piana, Loc. Garga – 87010 SARACENA (CS) – ITALY – Tel & fax +39.0981.480921

Internet: [www.starasphalt.com](http://www.starasphalt.com) - E-Mail: [info@starasphalt.com](mailto:info@starasphalt.com)

UNI EN ISO 9002 CERTIFICATE

SITEB ASSOCIATE MEMBER

